



CONNECTION TABLE

CAST NO.	D/F NO.	CAST NO.	D/F NO.
1	---	17	---
2	1	18	10
3	2	19	10
4	3	20	17
5	4	21	18
6	5	22	19
7	6	23	20
8	7	24	21
9	8	25	22
10	9	26	---
11	10	27	23
12	---	28	24
13	11	29	25
14	12	30	26
15	13	31	27
16	14	32	28

- NOTE:
1. ALL EXPOSED METALLIZED AREA SHALL BE GOLD PLATED 60 MICRO INCHES MIN. THK. OVER NICKEL PLATING UNLESS OTHERWISE SPECIFIED IN PURCHASE ORDER.
  2. INSULATION RESISTANCE: 100M AT 100V DC.
  3. LEAD RESISTANCE: 0.2 Ω MAX.
  4. FLATNESS PERTAINS METALLIZED PADS ONLY.
  5. SEAL AREA AND DIE ATTACH AREA SHALL BE ISOLATED FROM ANY LEADS. (ZERO GROUND)

MODIFICATIONS D. ADD. SHEET 22 CHANGE D/F LAYOUT CHANGE	DATE: 12/31/85 DRAWN: [Signature] CHECKED: [Signature] APPROVED: [Signature]	NAME: (700-320Z) 32 LCC 250 50 (AV11) SCALE: 10/1 MATERIAL: KYOCERA A-410	TOLERANCES: UNLESS OTHERWISE SPECIFIED 2:1 ± HUI ± 0.005	DESIGNED: [Signature] APPROVED: [Signature]
	KYOCERA CORPORATION KYOTO JAPAN	PB-089531		